

PODIUM DS65... Display Solutions for Outdoor Installation Environments




Active Display Area	65" Digital 36.5"W x 59.5"H [930mmW x 1510mmH] static
Resolution	3840x2160
Orientation	Portrait back-to-back
Aspect Ratio	16:9
Brightness	2500 nits digital and 350 nits static
Contrast	1200:1
Viewing Angle	178°
Display Colors	8 bit + FRC color depth display 1.07G colors
Connectivity	Ethernet/Wi-Fi/LTE
Environmental Rating	Outdoor
Mounting	Floor-standing
Mechanical Dimensions	80.7"H x 44.5"W x 12.2"D
Weight	500 lbs
Power (max)	900 to 1350W
Power Supply	120VAC 60HZ & 240VAC 50HZ
Player	BrightSign HS125
IP Rating	IP56
Glass (IK Rating)	4+4mm laminated AR with black serigraphic frit (IK08)
Operating Temperature	-4°F to 122°F
Certifications	UL62368, UL50e, FCC, CE, C-Tick

BrightSign HS145

Superior System-On-a-Chip (SoC) solution power by

BrightSignOS™



Video Engine	4K 8-bit at 60p 4K 10-bit at 30p Full HD at 60p
HTML5 Engine	HTML5, CSS, Javascript, SVG, WebGL and Chromium Compatibility
Video Media Formats	4K Video Codecs: H.265, H.264 4K Video Containers: .ts, .mov, .mp4, .mkv Full HD Video Codecs: H.265, H-264 (MPEG-4, Part 10), MPEG-2 Full HD Video Containers: .ts, .mpg, .vob, .mov, .mp4, .m2ts
Image Formats	.BMP, .JPEG, .PNG
Audio Formats (only applicable with availability of speakers)	.MP2, .MP3, .ACC, .WAV (AC3 is passed through)
Storage	256GB PCIe SSD and MicroSD Class 10
Connectivity	Ethernet/Wi-Fi/LTE