

Praevar Bar LCD Digital Display Display Solutions for indoor retail environments



Screen Size	24"	29"	37"	47.6"	58.4"	88"
Active Display Area	597.88*112.104m m	705.6*198.45mm	899.712*253.044 mm	1189.44*223.02m m	1428.48*401.76m m	2148.48*598.32m m
Resolution	1920x360	1920x540	1920x540	1920x360	3840x1080	3840x1080
Brightness	300 nits	700 nits	700 nits	700 nits	700 nits	700 nits
Contrast	1200:1	1200:1	4000:1	4000:1	4000:1	1100:1
Viewing Angle	178°	178°	178°	178°	178°	178°
Connectivity	AD/Windows/And roid	AD/Windows/And roid	AD/Windows/And roid	AD/Windows/And roid	AD/Windows/And roid	AD/Windows/And roid
Environmental Rating	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor
Mechanical Dimensions H x W x D	616*135*35mm	720.8*226.25*43. 3mm	914.91*280.84*43 .5mm	1198.64*240.82*3 5.23mm	1462.48*435.76*4 9.1mm	2179.5*629.4*86. 7mm
Weight	6.17 lbs	10.62 lbs	17.22 lbs	16.53 lbs	28.22 lbs	136.69 lbs
Power Consumption	≤28W	≤35W	≤50W	≤80W	≤120W	≤490W
Response Time	30ms	15ms	14ms	9ms	8ms	8ms
Operating Temperature	32°F to 122°F	32°F to 122°F	32°F to 122°F	32°F to 122°F	32°F to 122°F	32°F to 122°F
Working Life	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs	50,000Hrs	50,000Hrs

Commercial-in-confidence • Praevar Corporation